



11MAESTRO

Touch Screen, Single Channel, Power & Energy Monitor



*Also traceable to NRC-CNRC

Key Features

- **READS ALL HEADS**
 - Power: Thermopiles, Photo Detectors and Pyroelectrics
 - Energy: Thermopiles (in single shot mode) , Photo Detectors and Pyroelectrics
- **LARGE TOUCH SCREEN COLOR LCD DISPLAY**
 - 5.6" Diagonal
 - 640 x 480 Resolution
 - 18bit Color
 - FULLY Touch Screen Controls
- **UNIQUE ERGONOMIC DESIGN**
Great for both handheld and tabletop use, with improved rubber bands and quick stand for better stability
- **INTUITIVE USER INTERFACE**
Easy to navigate interface, with many display features:
 - Single or Dual Graph Display
 - Instant access to the main functions
 - Function Search tool
 - Interface available in multiple languages
- **USB KEY ACCESS**
Store data directly on a USB key
- **REAL-TIME STATISTICAL FUNCTIONS**
Max, Min, Average, Standard Deviation, RMS and PTP Stability, Pulse # and Repetition Rate
- **AVAILABLE OUTPUTS**
USB Key, Analog Output, RS-232, PC-USB, Ethernet


Connectivity





DUAL SCREEN DISPLAY

(SHOWN WITH SCOPE DISPLAY) With the Dual Screen mode, the 11MAESTRO really takes full advantage of its extra-large screen! Any display mode can be used in both single or dual display mode. In dual display mode, the Real Time display takes the upper portion of the screen, while any of the other displays (Scope, Needle, Averaging or Statistics) is set on the lower portion. The display in the lower portion can be easily changed using the parameters bar with drop-down menus in the center of the screen. You can also expand one of the displays to have it in Full Screen mode using the maximize button. Just as easily, you can go back to Dual Screen display by using the minimize button.



REAL TIME DISPLAY

This display shows the measured value in real time, with a corresponding bar graph below. The large size of the digits and high contrast of the graphics allow to see the measurement from a good distance. This mode is also always present in dual screen mode, in the upper portion of the screen.

- Very Large Digits
- Bar graph



SCOPE DISPLAY

With its line filling from the right of the screen, in a first-in/first-out manner, this display mode is a good approximation of an actual oscilloscope reading. Settings include time (x-axis) and range (y-axis). Basic statistics (can also be displayed directly on the screen).

- Oscilloscope-type graph
- On-screen, real time statistics (min, max and average)
- Fully customizable x and y axis



NEEDLE DISPLAY

Exactly like an analog needle, only faster! This mode is particularly useful when tuning a laser. The Real Time value is also displayed at the top of the screen.

- Ultra-fast readings
- Great for tuning
- Real Time value at the top of the screen
- Min and Max Values hold



AVERAGING DISPLAY

This very unique mode is perfect to show the trend of a laser over time. Set the number of points per batch and let the 11MAESTRO identify the minimum and maximum values of every batch. A yellow curve then follows the average of each batch, displayed as bars on the screen. The wider the difference between the white and blue portions of a bar (corresponding to the min and max values), the more unstable your laser is.

- Calculates the min, max and average values of batches of measurements
- Perfect to check laser stability over time

Specifications

11MAESTRO

DETECTOR TYPES	ALL MODELS: Thermopiles, Pyroelectrics, Photo Detectors
DISPLAY	Touch Screen 5.6in Color LCD
POWER METER SPECIFICATIONS	
Power Range	
Thermopile	1 μ W to 30 kW
Photo Detector	4 pW to 3 W
Monitor Accuracy	0.25 % \pm 5 μ V best scale
Statistics	Current Value, Max, Min, Average, Standard Deviation, RMS & PTP Stability, Time
ENERGY METER SPECIFICATIONS	
Energy Range	30 fJ to 30 kJ
Monitor Accuracy	\pm 1 % best scale
Software Trigger Level	0.1 to 99.9 %, 0.1 % resolution, default 2 %
Repetition Rate	2 000 Hz / 10 000 Hz in sampling
Real Time Data Transfer (To USB key)	2 000 Hz
Statistics	Current Value, Max, Min, Average, Std Dev., RMS & PTP Stability, Pulse #, Rep. Rate and Avg Power
DETECTOR COMPATIBILITY	
Thermopile	Average Power & Single Shot Energy
Photo Detector	Average Power & Pulse Energy
Pyroelectric	Pulse Energy & Average Power
GENERAL SPECIFICATIONS	
Interface Languages	English, German, French and Japanese (Chinese to come)
Digital Display Size	112.9 x 84.7 mm LCD - 640 x 480 pixels
Data Display	Real Time, Scope, Statistics, Digital Tuning Needle and Averaging
Analog Output	0-1 Volt, Full Scale, \pm 0.5 %
Rising Edge External Trigger	TTL Compatible, 2-25 V @ 0.4 mA
Serial Commands Via	USB (standard), Ethernet or RS-232 (cable in option)
Internet Upgrades Via	USB key
Data Storage Via	USB key
Dimensions	210W x 122H x 45D mm
Weight (With Batteries)	0.67 kg
Battery Type	4 x Rechargeable 1.2 V Ni-MH AA
Battery Life	6.5 hours
External Power Supply	100/240 VAC 50-60 Hz to 9 VDC 1.66 A
ORDERING INFORMATION	
Product Name	11MAESTRO

Specifications are subject to change without notice